



BL
A005

**Wetting
dispersant**

Product introduction

Unsaturated polyamide and polyester type

wetting and dispersing agent

Chemical composition

Unsaturated polyamide and polyester mixture

Features benefits

1. Effectively reduce the interfacial tension between the pigment and the binder;
2. For Yan, the filler has a good wetting effect, improve the efficiency of dispersion, reduce system viscosity;
3. Maintain good dispersion stability.

Recommended use

1. Dispersion and stability of inorganic pigments and matte powder;
2. Particularly suitable for the use of atomic ash and other high-filled unsaturated polyester system;
3. Industrial anti-corrosion coatings and general industrial paint;
4. Can also be used for organic pigments and carbon black wetting and dispersing.

Recommended dosage (100% active content)

Inorganic pigments	0.5-3%
Filler	0.2-1%
Organic pigments and low	
Surface carbon black	15-30%

Technical data

Active Ingredients:	98±2%
Color:	≤9
Density (g / cm ³):	0.91
Exterior:	Light yellow viscous liquid

Processing guidance

1. First, the product is uniformly dissolved in the grinding base material;
2. Add the pigment evenly after grinding.

Storage and transportation

1. Cool and dry and ventilated, below 60 °C, not close to the fire;
2. The shelf life of the sealed container is three years.

Package

25 kg or 200 kg drums.

We provide these data and technical advice with our existing knowledge. However, because of the different application environment, please users according to the test application, we can not guarantee all the circumstances.

JIANGSU BRILN EPT CO.,LTD.
Xinbei District Changzhou Jiangsu
Tel:0519-81884271 Fax:0519-85788271