



BL
A075

**Wetting and
dispersing
agent**

Product introduction

Unsaturated polyamide and polyester solution
wetting and dispersing agent

Chemical composition

Unsaturated polyamide and polyester solution

Feature advantages

1. Effectively reduce the interfacial tension between the pigment and the base;
2. It has good wetting effect on pigment and filler , improves dispersion efficiency and reduces system viscosity;
3. Maintain good dispersion stability.

Recommended use

1. Dispersion and stability of inorganic pigments and matte powders;
2. It is especially suitable for high-filling unsaturated polyester systems such as putty;
3. Industrial anti-corrosion coatings and general industrial paints;
4. It can also be used for wetting and dispersing of organic pigments and carbon black.

Recommended (100% active content)

dosage

Inorganic pigment	0.5-3%
Filler	0.2-1%
Organic pigments and low surface carbon black	15-30%

Technical data

Active ingredients:	70±2%
Chroma:	≤8
Density (g/cm ³):	0.87
Exterior:	Light yellow liquid

Processing guide

1. First dissolve the product evenly in the grinding base;
2. Add the pigment to disperse evenly and grind.

Storage and transportation

1. Cool and dry and ventilated, below 60 °C , not close to fire;
2. The shelf life of the sealed container is three years.

Package

25 kg or 200 kg drums.

We provide these data and technical advice with our existing knowledge. However, because of the different application environment, please users according to the test application, we can not guarantee all the circumstances.

JIANGSU BRILN EPT CO.,LTD.
Xinbei District Changzhou Jiangsu
Tel:0519-81884271 Fax:0519-85788271