



High gloss and high stability p-toluenesulfonic acid

Product introduction

High gloss and high stability blocked
p-toluene sulfonic acid for rapid reaction

Chemical composition

PTSA

Feature advantages

1. Help the paint to lower the baking temperature or shorten the time;
2. Improve coating gloss, hardness, corrosion resistance, hydrolysis resistance, solvent resistance, and excellent weather resistance;
3. Excellent storage stability.

Recommended use

1. Water and oil universal type;
2. Automotive refinish and general industrial baking varnish;
3. Coil and printed iron coatings.

Recommended dosage

0.5-3% of the total amount of paint.

Technical data

Solid content:	43±2%
Active ingredients:	26%
PH value:	6.0-7.0
Acid value:	3
Chroma:	≤1
Exterior:	Transparent yellowish liquid

Processing guide

1. Join in the latter part of production;
2. Stirring at medium and low speeds can be dispersed.

Storage and transportation

1. Cool and dry and ventilated, below 60 °C, not close to fire;
2. The shelf life of the sealed container is two year.

Package

25 kg drum or 180 kg large drum.

We provide these data and technical advice with our existing knowledge. However, because of the different application environment, please users according to the test application, we can not guarantee all the circumstances.

JIANGSU BRILN EPT CO.,LTD.
Xinbei District Changzhou Jiangsu
Tel:0519-81884271 Fax:0519-85788271