



### **Product Introduction**

Water and oil universal closed acid catalyst

### **Chemical composition**

Closed sulfonic acid mixture

### **Characteristic advantage**

1. Reduce the baking temperature, shorten the curing time;
2. Improve the film resistance to cooking, mechanical strength;
3. To improve the film hardness, gloss, moisture, corrosion.

### **Recommended use**

1. General industrial paint system, the high solid content;
2. Car bottom, surface, cover light, coil, home appliances paint;
3. Solvent type, water-based paint, emulsion system.

### **Recommended dosage**

The total amount of paint is 0.3-1.5%.

### **Technical data**

Active Ingredients:	50%
Solvent:	Alcohols and so on
Acid value:	92
Exterior:	Light yellow transparent liquid

### **Processing guidance**

Added later.

### **Storage and transportation**

1. Cool and dry and ventilated, below 60 °C, not close to the fire;
2. The shelf life of sealed containers is two year.

### **Package**

25 kg or 200KG package.

We provide these data and technical advice with our existing knowledge. However, because of the different application environment, please users according to the test application, we can not guarantee all the circumstances.

JIANGSU BRILN EPT CO.,LTD.  
Xinbei District Changzhou Jiangsu  
Tel:0519-81884271 Fax:0519-85788271